

New



High in quality, safety and versatility

POP-UP "THE WORLDS SMALLEST SCISSOR LIFT" JUST GOT THE '+ FACTOR, NOW REACHING UP TO 1 METRE HIGHER

POP-UP+ encompasses all the same features and benefits of its sister product Pop-up. The new model has been developed exclusively for indoor, low-level access but has the PLUS factor in allowing reach to a wider range of applications.

Key features and benefits

- Immediate low level access - 24 seconds to reach full platform height
- Easily deployed stabiliser system – provides quick access
- Safe – LED Lights confirm stabiliser set up
- Compact – 1200 x 700 mm footprint with stabilisers stowed
- Platform height – fully extended platform height of 2.50 mtrs gives an average working height of 4.50 mtrs
- Easy to manoeuvre – 'smooth roll' castors system fitted means it can be positioned by a single operative
- Easy to transport – compact size and weight means it fits onto a small flat back vehicle and can be delivered by a single person
- Easy to operate – simple hand set controls all elevation/de-elevation functions
- Training – product training available
- Affordable – very competitively priced (offers good price comparison to other low level access equipment solutions)
- Battery powered with universal charger – low usage and ownership costs
- Over 150 operations on one battery charge – can accommodate heavy 'daily' usage requirements.



>>...SLIPS INTO LIFTS...



>>...AND THROUGH DOORS...



>>...EASY TO OPERATE...

Same POP-UP features PLUS extra 1 metre working height



Pop On - Pop Up - Pop Off



High in quality, safety and versatility

Production Specification

POP-UP+ has been designed, manufactured and tested in accordance with both the European Standard EN280 and the safety requirements of the European Machinery Directive 98/37/EC.

Load

Safe working load (SWL)	240 kg
Equivalent to	1 person + 160 kg tools and materials

Dimensions

Maximum platform height	2.50 metres
Maximum working height	4.50 metres
Platform length	1.01 metres
Platform width	0.52 metres
Footprint (stabilisers deployed)	1.30 metres
Footprint (stabilisers stowed)	0.70 metres
Platform guard rail height	1.10 metres
Toe board height	0.15 metres
Toe board height (gate end)	0.10 metres
Maximum allowable manual force	200 Newtons
Maximum allowable wind speed	0 metres/sec
Maximum allowable Chassis inclination	0 degrees

Electrical system

Voltage	12 volt DC
Motor	0.7 kW
Battery	80Ah
Battery charger	Automatic multi-voltage

Hydraulic system

Maximum pressure	250 bar
Reservoir capacity	1 litre

Function speeds (approx.)

Raise	24 seconds
Lower	25 seconds
Approx number of lifts	150 (fully charged with SWL)

Stowed dimensions

Overall length	1.20 metres
Overall height	1.80 metres
Overall width	0.700 metres

Weight

Overall mass (GVW)	365 kg
Maximum wheel load	350 kg



skyreach
access solutions

Sky House, Daurada Drive, Stafford,
Staffordshire, ST17 U.K.

Tel: + 44 (0) 1785 244177 Fax: + 44 (0) 1785 229874

www.skyreachaccess.com

